

# Sprint 350

Direct connected three-phase energy meter



Import/export  
metering



Revenue  
protection



Interoperable  
communication

## Interoperable comms with advance event detection for consumer metering

Sprint 350 is an enhanced metering solution for three-phase direct-connected installations. It is suitable for domestic, industrial and commercial applications. It has advanced revenue protection features, making it especially useful in areas where theft and fraud are prevalent.



### Application

- Direct connected domestic, industrial and commercial billing
- Sub metering for residential, small industrial and commercial establishments
- Remote data collection for billing and consumption analysis

### Benefits

- A wide range catering to various utilities requirement
- Power factor recording for reactive power management
- Revenue protection

### Features

- Single vector/bi vector/tri vector measurement
- Time of day metering with maximum demand registration and automatic billing
- Phase indicators for healthiness of voltages
- Backlight LCD display with annunciators for various critical events
- Forwarded energy registration under current reversal condition
- Scroll lock feature for continuous display of desired parameter
- High resolution energy mode for dial test
- Interoperable DLMS protocol for meter reading with option for remote reading port
- Advanced tamper detection features for voltage, current and magnetic influences
- Two separate metrology LEDs for accuracy testing of different energy types
- Meter reading in the absence of mains supply using internal battery



## Technical specifications

### Electrical

Connection type	Direct connected
Wiring configuration	3-phase 4-wire
Voltage range	230/240 V (P-N), 400/415 V (P-P)
Current range	5-30 A, 10-40 A, 10-60 A, 20-100 A
Accuracy	Class 1.0
Mains frequency	50 Hz $\pm$ 5%
Burden	As per standards

### Compliance

Standards*	IS 13779, IEC 62052-11, IEC 62053-21, DLMS Indian Companion Standard
------------	--

### Mechanical

Dimensions (W x H x D)	191 x 255 x 82 mm (approx.)
Weight	2 kg (approx.)
Enclosure	Engineering plastic
Sealing	Provision of sealing on mains cover and terminal cover

### Environmental

Degree of protection	IP 51
Insulation class	Protective class II
Temperature	-10 °C to +55 °C (operating)   -25 °C to +70 °C (storage)
Humidity	95% non-condensing

### Features

Tariff rate registers	Up to 8 rate registers, for two energy channels
Maximum demand	Up to 2 types, configurable in 8 registers
Load survey	Up to 70 days load profile for 8 parameters (configurable), with 30 minute integration period
Communication	Optical port for local communication, optional RS232 (RJ11 port) for remote communication

Contact your nearest sales office for more details

#### Australia

[sales\\_australia@securemeters.com](mailto:sales_australia@securemeters.com)  
[www.securemeters.com/au](http://www.securemeters.com/au)

#### Dubai

[sales\\_middleeast@securemeters.com](mailto:sales_middleeast@securemeters.com)  
[www.securemeters.com/me](http://www.securemeters.com/me)

#### Europe

[sales\\_europe@securemeters.com](mailto:sales_europe@securemeters.com)  
[www.securemeters.com/eu](http://www.securemeters.com/eu)

#### India, SE Asia, Africa

[sales\\_india@securemeters.com](mailto:sales_india@securemeters.com)  
[www.securemeters.com/in](http://www.securemeters.com/in)

#### UK

[sales\\_uk@securemeters.com](mailto:sales_uk@securemeters.com)  
[www.securemeters.com/uk](http://www.securemeters.com/uk)